

# Kiosk Profi

Innovative, versatile & efficient



# Profi (A2+)

## The all-purpose A2 Scanner

The book2net Profi is one of the most successful and versatile A2 book scanners on the international market and impresses with its exceptional image quality, smooth operating and high productivity. Fragile historical books, modern books, magazines, documents, files or ring binders – thanks to its self-adjusting book cradle, the book2net Profi can handle a wide variety of documents. The removable Makrolon® plate also enables scanning with or without pressure.

With its high depth of field and integrated optical book fold optimization (BFO), the book2net Profi delivers constant image sharpness across the entire original surface. This gives you excellent scanning results even with wavy surfaces.

## ■ High-perfomance sensor

- High-resolution CMOS area sensor
- Selectable options: 300 ppi / 400 ppi / 600 ppi
- 0.3 sec. scanning time (double page, color at 400 ppi)
- 2.2 sec. processing time (scanning + imaging + storage)
- USB 3.0 interface
- Optimized for OCR applications due to reduced noise

#### ■ LED Illumination

- Cold light LEDs
- Fresnel lenses for homogeneous, uniform illumination Constant wavelength
- Exposure time 0.5 sec.
- Adaptable to ambient light
- Eco function
- Low energy consumption

## ■ Eco-friendly

- No UV / IR radiation
- No ozone, no emission
- No heat load
- Lowest noise emission
- Low Energy Control (LEC)
- Energy-saving

## 23" Touchscreen (optional)

- Ergonomic touchscreen
- Optimal user-friendliness
- Zoom and proof monitor functionality
- Industrial standard





- Self-adjusting
- 15 cm height adjustment
- 10 cm spine exemption
- Motorized locking
- Scan initialization via smooth touch

HIGHTECH FOR HERITAGE

Preservation approved

### Optics

- Schneider-Kreuznach precision lens
- Depth of field 12 cm
- Brilliant color rendering
- Perfect linearity
- Distortion-free
- Longevity guaranteed

#### External PC

- Optional book2net PC or customer PC
- Latest design
- Built-in version (optional)

## ■ 3D Analyzer

- Geometric book analysis via area sensor
- Finger removal
- Edge detection
- Page recognition
- Type area detection
- Book fold optimization (BFO)
- Preservation approved

#### ■ Software & Features

- Live Video Preview
- Easy Scan / bookScan professional scan software
- OCR (optional)
- Live Control Professional (optional)

## Color Management

### Integrated True Color Management:

METAMORFOZE, FADGI, ISO/TS 19264:1 2017 standard in terms of color quality, resolution, noise & linearity

## Scanner specifications

## Technical data

Shutter  No shutter mechanics  Cold-light LED-technology with integrated Light- Control- System (LCS)  Resolution  Depth of field  12 cm  Scanning time  0.3 seconds (A2 color at 400 ppi)  Processing time  2.2 seconds (scanning + imaging + storage)  Layout section  460 mm x 645 mm  PC interface  USB 3.0  EasyScan / bookScan professional intuitive scan software with extended functions for job management, image editing and further processing  Color depth  48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/w  TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW  Output  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions  680 x 940 x 1215 mm (wx d x h)  Weight  Connection values  100 V - 240 V, 47 Hz - 63 Hz  Energy consumption  Standby 34 dB(A), in operation 39 dB(A)	Sensor	High performance CMOS sensor
Illumination	Optics	Schneider-Kreuznach precision lens
Resolution  System (LCS)  Resolution  300 ppi / 400 ppi / 600 ppi  Depth of field  12 cm  Scanning time  0.3 seconds (A2 color at 400 ppi)  Processing time  2.2 seconds (scanning + imaging + storage)  Layout section  460 mm x 645 mm  PC interface  USB 3.0  EasyScan / bookScan professional intuitive scan software with extended functions for job management, image editin, and further processing  Color depth  48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/w  File formats  TIFF, JPEG, JPEG 2000, PNG, PDF-A, multipage PDF and multipage TIFF, RAW  Output  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions  680 x 940 x 1215 mm (w x d x h)  Weight  Connection values  100 V - 240 V, 47 Hz - 63 Hz  Energy consumption  Standby 50 VA, in operation 100 VA  Noise emission  Standby 34 dB(A), in operation 39 dB(A)	Shutter	No shutter mechanics
Depth of field  Scanning time  0.3 seconds (A2 color at 400 ppi)  Processing time  2.2 seconds (scanning + imaging + storage)  Layout section  460 mm x 645 mm  PC interface  USB 3.0  EasyScan / bookScan professional intuitive scan software with extended functions for job management, image editing and further processing  Color depth  48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/w  File formats  TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions  680 x 940 x 1215 mm (w x d x h)  Weight  Connection values  100 V - 240 V, 47 Hz - 63 Hz  Energy consumption  Standby 50 VA, in operation 100 VA  Noise emission  Standby 34 dB(A), in operation 39 dB(A)	Illumination	Cold-light LED-technology with integrated Light- Control- System (LCS)
Scanning time  O.3 seconds (A2 color at 400 ppi)  Processing time  2.2 seconds (scanning + imaging + storage)  Layout section  460 mm x 645 mm  PC interface  USB 3.0  EasyScan / bookScan professional intuitive scan software with extended functions for job management, image editing and further processing  Color depth  48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/w  File formats  TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions  680 x 940 x 1215 mm (w x d x h)  Weight  Connection values  100 V - 240 V, 47 Hz - 63 Hz  Energy consumption  Standby 50 VA, in operation 100 VA  Noise emission  Standby 34 dB(A), in operation 39 dB(A)	Resolution	300 ppi / 400 ppi / 600 ppi
Processing time  2.2 seconds (scanning + imaging + storage)  460 mm x 645 mm  PC interface  USB 3.0  EasyScan / bookScan professional intuitive scan software with extended functions for job management, image editing and further processing  Color depth  48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/w  TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW  Output  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions  680 x 940 x 1215 mm (w x d x h)  Weight  Connection values  100 V - 240 V, 47 Hz - 63 Hz  Energy consumption  Standby 34 dB(A), in operation 39 dB(A)	Depth of field	12 cm
Layout section 460 mm x 645 mm  PC interface USB 3.0  EasyScan / bookScan professional intuitive scan software with extended functions for job management, image editing and further processing  Color depth 48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/w  TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions 680 x 940 x 1215 mm (w x d x h)  Weight approx. 70 kg  Connection values 100 V - 240 V, 47 Hz - 63 Hz  Energy consumption Standby 50 VA, in operation 100 VA  Noise emission Standby 34 dB(A), in operation 39 dB(A)	Scanning time	0.3 seconds (A2 color at 400 ppi)
PC interface  EasyScan / bookScan professional intuitive scan software with extended functions for job management, image editing and further processing  Color depth  48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/w  TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions  680 x 940 x 1215 mm (w x d x h)  Weight  Connection values  100 V - 240 V, 47 Hz - 63 Hz  Energy consumption  Standby 50 VA, in operation 100 VA  Noise emission	Processing time	2.2 seconds (scanning + imaging + storage)
EasyScan / bookScan professional intuitive scan software with extended functions for job management, image editing and further processing  Color depth 48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/w  TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions 680 x 940 x 1215 mm (w x d x h)  Weight approx. 70 kg  Connection values 100 V - 240 V, 47 Hz - 63 Hz  Energy consumption Standby 50 VA, in operation 100 VA  Noise emission Standby 34 dB(A), in operation 39 dB(A)	Layout section	460 mm x 645 mm
Softwarewith extended functions for job management, image editing and further processingColor depth48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/wFile formatsTIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAWOutput\$RGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standardDimensions680 x 940 x 1215 mm (w x d x h)Weightapprox. 70 kgConnection values100 V - 240 V, 47 Hz - 63 HzEnergy consumptionStandby 50 VA, in operation 100 VANoise emissionStandby 34 dB(A), in operation 39 dB(A)	PC interface	USB 3.0
TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions  680 x 940 x 1215 mm (w x d x h)  Weight  approx. 70 kg  Connection values  100 V - 240 V, 47 Hz - 63 Hz  Energy consumption  Standby 50 VA, in operation 100 VA  Noise emission  TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  100 V - 240 X 1215 mm (w x d x h)  Standby 50 VA, in operation 100 VA  Standby 34 dB(A), in operation 39 dB(A)	Software	with extended functions for job management, image editing
and multipage TIFF, RAW  SRGB, Adobe 1998 RGB, eciRGB V1/V2, ProPhoto and according to ICC standard  Dimensions  680 x 940 x 1215 mm (w x d x h)  Weight  approx. 70 kg  Connection values  100 V - 240 V, 47 Hz - 63 Hz  Energy consumption  Standby 50 VA, in operation 100 VA  Noise emission  Standby 34 dB(A), in operation 39 dB(A)	Color depth	48 bit color; 24 bit color, 16 bit gray, 8 bit gray; 1 bit b/w
Dimensions  680 x 940 x 1215 mm (w x d x h)  Weight  approx. 70 kg  Connection values  100 V - 240 V, 47 Hz - 63 Hz  Energy consumption  Standby 50 VA, in operation 100 VA  Noise emission  Standby 34 dB(A), in operation 39 dB(A)	File formats	TIFF, JPEG, JPEG 2000, PNG, PDF, PDF-A, multipage PDF and multipage TIFF, RAW
Weightapprox. 70 kgConnection values100 V - 240 V, 47 Hz - 63 HzEnergy consumptionStandby 50 VA, in operation 100 VANoise emissionStandby 34 dB(A), in operation 39 dB(A)	Output	
Connection values100 V - 240 V, 47 Hz - 63 HzEnergy consumptionStandby 50 VA, in operation 100 VANoise emissionStandby 34 dB(A), in operation 39 dB(A)	Dimensions	680 x 940 x 1215 mm (w x d x h)
Energy consumptionStandby 50 VA, in operation 100 VANoise emissionStandby 34 dB(A), in operation 39 dB(A)	Weight	approx. 70 kg
Noise emission Standby 34 dB(A), in operation 39 dB(A)	Connection values	100 V - 240 V, 47 Hz - 63 Hz
	Energy consumption	Standby 50 VA, in operation 100 VA
Safety standard CE EMV	Noise emission	Standby 34 dB(A), in operation 39 dB(A)
	Safety standard	CE EMV

Maintenance possible via remote service.



## Profi in use

- The Historical Archive of the City of Cologne
- The National Library of Uzbekistan











#### **MICROBOX**

Martin J. French book2net UK & Ireland +44 (0) 7368 495 121 martin@lensart.uk

www.book2net.uk

Quality made in Germany book2net is a brand of MICROBOX

